

SEMIAUTOMATIC SHOTGUN - SUPERIOR LINE - ENGRAVED VERSION



8. HAND ENGRAVED



9. SUPERIOR 1 - BLACK NICKEL LASER ENGRAVED



10 SUPERIOR 3 - BLACK NICKEL LASER ENGRAVED



SEMIAUTOMATIC SHOTGUN CAL. 12/3" (76 mm)

Receiver	Aluminium alloy (ERGAL) / PATENTED outline / Protection: black anodized finish / Additional protection: different types
Barrel	Made out of SAE4140 steel, ultrasonic checked / Lengths: 24" (610 mm) - 26" (660 mm) - 28" (710 mm) - 30" (760 mm) / Inner chokes for use of steel pellets too / Chrome-lined barrel / Blue finish / Breech screwed in to barrel / Brass sight / Optic fiber sight / 7 mm (0,275") ventilated rib
Bolt	Rotating head / Combined with double rod integral to the sleeve. PATENTED
Stock	Standard varnished walnut with Micro Gel recoil pad, extra soft / Length 365 mm from trigger / Laser checkering
Forend	Varnished standard walnut, laser checkered / PATENTED locking device
Magazine	Max capacity with magnum 3" cartridges: 4+1 / Max capacity with standard 2 3/4" cartridges: 5+1
Triggerguard	Fiberglass reinforced technopolymer / With right or left manual safety on the trigger / With automatic safety on the bolt locking
Cut-Off	Automatic, Useful for the cartridge change in the chamber
Ejector	Flexible, mounted on receiver
Operation	INERTIAL OR GAS OPERATED SYSTEM
Weight	Kg 2,800 - 3,100



SEMIAUTOMATIC SHOTGUN CAL. 20/3" (76 mm)

Receiver	Aluminium alloy (ERGAL) / PATENTED outline / Protection: black anodized finish / Additional protection: different types
Barrel	Made out of SAE4140 steel, ultrasonic checked / Lengths: 24" (610 mm) - 26" (660 mm) - 28" (710 mm) / Inner chokes for use of steel pellets too / Chrome-lined barrel / Blue finish / Breech screwed in to barrel / Brass sight / Optic fiber sight / 7 mm (0,275") ventilated rib
Bolt	Rotating head / Combined with double rod integral to the sleeve. PATENTED
Stock	Standard varnished walnut with Micro Gel recoil pad, extra soft / Length 365 mm from trigger / Laser checkering
Forend	Varnished standard walnut, laser checkered / PATENTED locking device
Magazine	Max capacity with magnum 3" cartridges: 4+1 / Max capacity with standard 2 3/4" cartridges: 5+1
Triggerguard	Fiberglass reinforced technopolymer / With right or left manual safety on the trigger / With automatic safety on the bolt locking
Cut-Off	Automatic, Useful for the cartridge change in the chamber
Ejector	Flexible, mounted on receiver
Operation	INERTIAL OR GAS OPERATED SYSTEM
Weight	Kg 2,800 - 3,100